



HF Industrial Reader Advant SR 1CH

Applications

- Industrial Automation
- Asset Tracking
- Laundry Management
- Access Control

Features

- HF (ISO 14443A/B, ISO 15693, ISO 18000-3)
- Solutions for Near Field, Short- & Mid-Range applications
- Possibility of using different RFID Standards parallel in one Application
- Read Modes: Buffered Read Mode, Scan Mode and Notification Mode
- Integrated I/O Ports
- Diagnostic Mode via USB
- Multiple Interface Options
- Ruggedized Product Design and Enclosure
- Common SDK for all BLUEBOX Products
- BLUEBOX SHOW Applications Software

Description

The Industrial Reader Advant SR 1CH is a read/write device with one antenna port. This powerful HF reader can achieve a reading distance up to 15 cm. Advant SR with one channel allows for Near-Field and Short-Range applications.

The combination of a modern RFID module and an up-to-date controller engine enables a fast data processing and high reading rates in one device. iDTRONIC's powerful BLUEBOX SDK allows the fast development of extensive applications.

Technical Data

Mechanical Specifications	
Housing-Material	Aluminium
Dimensions	110 x 140 x 60 mm
Weight	ca. 430 g
Protection Class	IP65

Electrical Specifications	
Power Supply	24 VDC \pm 10 %
Power Consumption	3 W
Operating Frequency	13.56 MHz
Operating Distance	up to 15 cm
Memory Extension	Micro SD-Slot
Connectors	M12
Digital I/O	2 (opto-isolated)
Antenna Connector	1x Lumberg
Interfaces	Ethernet, RS232/RS485, Profibus, Profinet, Modbus (TCP)

Features	
Status Display	4/8 LEDs
Working Modes	Scan Mode, Notification Mode, Buffered Read Mode, Stand-alone Mode
Integrated Webserver	Remote Configuration & Standalone Mode
Temperature Sensor	On-board
Service Interface	USB

Environmental Conditions	
Operating Temperature	-20°C to +65 °C
Humidity	5% to 95%

Supported Standards / Tags	
ISO 14443A/B, ISO 15693, ISO 18000-3, NXP MIFARE family	

Applicable Standards	
EMC	EN 301 489-3
Radio Regulation	EN 302 208-2
Safety	CEI EN 60950-1, CEI EN 50364

SDK Information	
Supported OS	Windows 7, 8
Supported Languages	C#, C++, serial command protocol

*Reading distance depends on tag, antenna and environmental conditions

Order Codes

Version	Order Code
RS232/RS485	R-IN-HF-5231H
Ethernet	R-IN-HF-5232H
Profibus	R-IN-HF-5233H
Modbus	R-IN-HF-5242H-MB

iDTRONIC GmbH
 Donnersbergweg 1
 67059 Ludwigshafen
 GERMANY

Phone +49 (0) 621 66 90 09 4-0
 Fax +49 (0) 621 66 90 09 4-9
 E-Mail: info@idtronic-rfid.com
 Web: idtronic-rfid.com

For further information & prices, please contact info@idtronic-rfid.com

Subject to alteration without prior notice
 ©2015 iDTRONIC GmbH