

# Asset | Logistic Tags

## WASTE BIN TAGS



### APPLICATIONS

- Waste Management

### FEATURES

- Pa 6, potting PUR Material
- IP66 Protection Class
- Black Coloured
- RFID LF

### RFID OPTIONS

- LF (134.2 kHz or 125 kHz)

### PRODUCT DESCRIPTION

The Waste Bin Tags from iDTRONIC were designed to fit into the most common residential garbage cans.

They can easily be inserted into the existing holes for RFID transponders. The tags are also designed to be read from different directions. The tags are ideal for side and rear lift applications.

iDTRONIC's Waste Bin Tag is available in LF: 134.2 kHz (FDX-B or HDX) or 125 kHz.

## TECHNICAL DATA

### PRODUCT SPECIFICATIONS

Material	Pa 6, potting PUR
Antenna Type	Wired
Reading Distance	Up to 6 cm
Dimensions	ø 30 × 15 mm
Weight	10 g
Colour	Black
Protection Class	IP 66
Applicable Temperature	- 25 °C to + 90 °C

### AVAILABLE LF: 125 KHZ ICS

IC TYPE	MEMORY SIZE	MEMORY MODE	PROTOCOL
EM 4100/4200	8 Byte	Read-only	ISO 11784
NXP Hitag S256	256 Byte	R/W	ISO 11785

**OTHER ICS ARE AVAILABLE ON REQUEST!**

iDTRONIC GmbH  
Donnersbergweg 1  
67059 Ludwigshafen  
GERMANY

Phone +49 (0) 621 66 90 09 4-0  
Fax +49 (0) 621 66 90 09 4-9  
E-Mail: [info@idtronic-rfid.com](mailto:info@idtronic-rfid.com)  
Web: [idtronic-rfid.com](http://idtronic-rfid.com)

For further information & prices, please contact [info@idtronic.de](mailto:info@idtronic.de)

Subject to alteration without prior notice  
©2019 iDTRONIC GmbH