

UHF Embedded Antennas



APPLICATIONS

- Label Encoding
- Self-Check In / Out
- Handheld Computer
- Product Identification
- Access Control

FEATURES

- Supports UHF Frequency
- 4 different Sizes
- RHCP (Circular Polarized)
- U.FL or SMA female

RFID OPTIONS

- **UHF** (868 ±4 MHz or 922 ±4 MHz)

PRODUCT DESCRIPTION

These circular polarised Embedded Antennas are especially designed for operation in the EU or US UHF RFID band.

Their small-band design allows an extra in gain, so with this small form-factor a maximum can be achieved. Our UHF Antennas are perfect for integration into mobile devices, self-checkout system and much more applications. They are available with U.FL or SMA female connector.

You have the choice of four various sizes, according to your storage and application needs.

TECHNICAL DATA


A901



PRODUCT SPECIFICATIONS

Product Description	Embedded Antenna for UHF frequency
Operating Frequency	868 ±4 MHz or 922 ±4 MHz
Gain	4 dBic
Polarisation	Right hand circular polarised (RHCP)
Bandwidth (MHz)	10
V.S.W.R	1.3:1
Impedance	50 Ohms
RF Cable	RG174 (10 cm)
RF Connector	U.FL
Dimensions	Groundplate: 90 × 90 × 6 mm Antenna: 64 × 64 mm
Operating Temperature	-10 °C to +55 °C

A902



PRODUCT SPECIFICATIONS

Product Description	Embedded Antenna for UHF frequency
Operating Frequency	868 ±4 MHz
Gain	-1 dBic
Polarisation	Right hand circular polarised (RHCP)
Bandwidth (MHz)	2
V.S.W.R	1.5:1
Impedance	50 Ohms
RF Cable	RG174 (10 cm)
RF Connector	U.FL
Dimensions	Groundplate: 40 × 40 × 5 mm Antenna: 36 × 36 mm
Operating Temperature	-10 °C to +55 °C


A903



PRODUCT SPECIFICATIONS

Product Description	Embedded Antenna for UHF frequency
Operating Frequency	864 MHz - 868 MHz (EU) 902 MHz - 928 MHz (US)
Gain	-13 dBic
Polarisation	Right hand circular polarised (RHCP)
Bandwidth (MHz)	2
V.S.W.R	2.0:1
Impedance	50 Ohms
RF Connector	SMA female
Dimensions	Groundplate: 25 × 25 × 1.5 mm Antenna: 18.5 × 18.5 × 2 mm
Operating Temperature	-20 °C to +55 °C

A904



PRODUCT SPECIFICATIONS

Product Description	Embedded Antenna for UHF frequency
Operating Frequency	868 ±4 MHz
Gain	-1 dBic
Polarisation	Right hand circular polarised (RHCP)
Bandwidth (MHz)	2
V.S.W.R	1.5:1
Impedance	50 Ohms
RF Cable	RG174 (10 cm)
RF Connector	U.FL
Dimensions	Groundplate: 70 × 70 × 5 mm Antenna: 36 × 36 mm
Operating Temperature	-10 °C to +55 °C

ORDER CODES

VERSIONS	ORDER CODES
A901	OEM-UHF-A901-GP-UFL
A901 (FCC)	OEM-UHF-GP-A901-UFL-FCC
A902	OEM-UHF-A902-GP-UFL
A903	OEM-UHF-A903-GP-SMA
A903 (FCC)	OEM-UHF-GP-A903-SMA-FCC
A904	OEM-UHF-A904-GP-UFL

iDTRONIC GmbH
Ludwig-Reichling-Straße 4
67059 Ludwigshafen
GERMANY

Phone +49 (0) 621 66 90 09 4-0
Fax +49 (0) 621 66 90 09 4-9
E-Mail: info@idtronic-rfid.com
Web: idtronic-rfid.com

For further information & prices, please contact info@idtronic-rfid.com

Subject to alteration without prior notice
©2020 iDTRONIC GmbH